

MAHARSHI DAYANAND UNIVERSITY ROHTAK
(Established under Haryana Act No. 25 of 1975)
'A+' Grade University accredited by NAAC

DEPARTMENT OF FORENSIC SCIENCE

No.FS./2022/ 1285-88
Dated; - 20/12/22

To, O/C

Dear Sir/Madam

Please quote for article mentioned below in the list attached herewith so as reach undersigned by 10th Jan 2023.

THE QUALITY, MAKE, PACKING and other particulars of each item should be stated.

WHILE SUBMITTING THE QUOTATIONS PLEASE NOTE THE POINTS MENTIONED BELOW: -

1. The quotations are to be sent in an envelope marked QUOTATION DUE ON 10th Jan 2023 and this envelope may be put in another envelope addressed to the undersigned.
2. The rates of S.T./ C.S.T., EXCISE, CUSTOM and other takes chargeable must be specified.
3. The rates of insurance, if any, should be specified. The firm will be required to submit the original Payee Receipt along with the bill.
4. Please state the time period within which the items will be supplied.
5. GUARANTEE PERIOD OF THE INSTRUMENTS MUST BE MENTIONED.
6. Discount if any, is to be given with the quotation.

Sr. No.	Name of Item	Specifications
1.	Stereo-zoom camera and digital unit	<ul style="list-style-type: none">• 9.7" High resolution touch screen, 5.0-megapixel camera with C mount in-built software• USB Digital camera with C mount and software• Supported with HDMI output• USB storage with SD card storage facility
2.	Abbe's Refractometer (Digital)	<ul style="list-style-type: none">• Digital Refractometer with software and Standards• Measurement range- (Refractive index) 1.300-1.700• Refractive index accuracy- ± 0.0002• Temperature range- 0-50 °C• Correcting range of BX vs temp. 15-45°C• Dimensions(mm)- 330×180×380
3.	Electrode for pH meter model ION 2700 pH meter (Oakton)	<ul style="list-style-type: none">• Range- 0-13 pH• Temperature- 0-100 °C• material glass• Measuring section size: $\phi 12 \times 110$mm• Liquid junction material: Ceramic• Inner pole: Ag/AgCl• BNC connector type• Double junction, Refillable
4.	Weighing balance	<ul style="list-style-type: none">• Analytical balance• Capacity: 310 g• Least count: 0.01g• Pan diameter- $\phi 110$mm• Dimensions- 342.5×212×27.1mm

5.	Vortex shaker/mixer	<ul style="list-style-type: none"> • Adjustable speed from 300 to 4200 RPM & timer setting • Digital display – Shows speed and time alternatively at every 5 secs • User enabled run time and off time setting • 3-way switch (On/Off/Touch) with Power On LED • Orbital diameter of 4 mm
6.	Data logger with probe (Temperature & Humidity)	<ul style="list-style-type: none"> • Temperature range: -30°C~+60°C; • Temperature accuracy: -30°C~+60°C, • Humidity range: 0~99%RH • Humidity accuracy: ±3%RH (25°C,20~90%RH), • Record data capacity: RC-4HA 8000 points • Record interval: 10 s~24 hour adjustable • Battery life: if the record interval sets as 15 minutes it could be used above one year.

Yours Sincerely.



Head, Deptt. Of Forensic Science
M.D. University, Rohtak
Head
Department of Forensic Science
Maharshi Dayanand University
Rohtak-124001 (Haryana)